

SEA&LAND ELECTRONIC CORP.

13F., No.120-10,
 Sec. 3, Zhongshan Rd., Zhonghe Dist., New Taipei City 235,
 Taiwan

Tel.: 886-2-8221-2567

Fax.: 886-2-2225-7268

Techfuse
PTC Devices
 Resettable Fuse

PRODUCT: SMD300L

DOCUMENT: QR0429

ECN. NO.:

REV LETTER:

REV DATE: 2014/12/29

PAGE NO.: 1 of 1

Specification Sheet

Terminal Pad Solderability:
 Meets EIA Specification RS186-9E
 And ANSI/J-STD-002 Category 3.

Terminal Pad Materials:
 Tin-plated Nickel-Copper

Lead-Free, RoHS Compliant

Marking:

α Alpha Logo
 300L Part Identification




TABLE I. DIMENSIONS:

Model	A		B		C		D	E
	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MIN
SMD300L	6.73	7.98	4.80	5.44	0.50	1.30	0.30	0.25

Unit:mm

TABLE II. PERFORMANCE RATINGS:

Model	V_{max} (V)	I_{max} (A)	I_{hold} @25°C (A)	I_{trip} @25°C (A)	P_d Typ. (W)	Maximum Time To Trip		Resistance	
						Current (A)	Time (Sec)	$R_{i_{min}}$ (Ω)	$R_{1_{max}}$ (Ω)
SMD300L	6	40	3.00	6.00	1.500	8.0	20.0	0.012	0.048

Order Information

Packaging

SMD2920	300	-6V	Tape & Reel Quantity
Product name	Hold	Max	2000 pcs/reel
Size 7555 mm / 2920 mils	Current	voltage	
SMD: surface mount device	3.00A		

Recognition: UL Approved.

E201504/E319079

