

SEA&LAND ELECTRONIC CORP.

13F., No.120-10,
 Sec. 3, Zhongshan Rd., Zhonghe Dist., New Taipei City 235,
 Taiwan
 Tel.: 886-2-8221-2567
 Fax.: 886-2-2225-7268

Techfuse
PTC Devices
 Resettable Fuse

PRODUCT: SL1206600
 DOCUMENT: QR0429
 ECN. NO.:
 REV LETTER:
 REV DATE: 2026/4/28
 PAGE NO.: 1 of 1


Specification Sheet

Terminal Pad Solderability:
 Meets EIA Specification RS186-9E
 And ANSI/J-STD-002 Category 3.

Terminal Pad Materials:
 Tin-plated Nickel-Copper

Lead-Free, RoHS Compliant

Marking:
 Part Identification

**TABLE I. DIMENSIONS:**

Model	Marking	A		B		C		D	E	Unit:mm
		Min.	Max.	Min.	Max.	Min.	Max.	Min.	Min.	
SL1206600		3.00	3.50	1.50	1.85	0.60	1.30	0.25	0.10	

TABLE II. PERFORMANCE RATINGS:

Model	Marking	V_{max} (Vdc)	I_{max} (A)	I_{hold} @25°C (A)	I_{trip} @25°C (A)	P_d Typ. (W)	Maximum Time To Trip		Resistance	
							Current (A)	Time (Sec)	$R_{i_{min}}$ (Ω)	$R_{1_{max}}$ (Ω)
SL1206600		6	50	6.0	12.0	1.5	20.0	5.0	0.001	0.010

Order Information**Packaging**

SL1206	600	Tape & Reel Quantity	
Product name	Hold Max	3000 pcs/reel	
Size 3216 mm / 1206 mils	Current voltage		
SL: surface mount device	6.00A		

Recognition:

2015/863/EU



EN14582

