

SEA&LAND ELECTRONIC CORP.

13F., No.120-10,
 Sec. 3, Zhongshan Rd., Zhonghe Dist., New Taipei City 235,
 Taiwan
 Tel.: 886-2-8221-2567
 Fax.: 886-2-2225-7268

Techfuse
PTC Devices
 Resettable Fuse

PRODUCT: SMD0603-050
 DOCUMENT: QR0429
 ECN. NO.:
 REV LETTER: A
 REV DATE: 2011-3-29
 PAGE NO.: 1 of 1

Specification Sheet

Terminal Pad Solderability:
 Meets EIA Specification RS186-9E
 And ANSI/J-STD-002 Category 3.

Terminal Pad Materials:
 Tin-plated Nickel-Copper

Lead-Free, RoHS Compliant

Marking:
 Part Identification
 5 = 050




TABLE I. DIMENSIONS:

Model	Marking	A		B		C		D
		Min.	Max.	Min.	Max.	Min.	Max.	Min.
SMD0603-050	5	1.45	1.85	0.65	1.05	0.50	1.10	0.15

Unit:mm

TABLE II. PERFORMANCE RATING:

Model	Marking	V _{max} (Vdc)	I _{max} (A)	I _{hold} @25°C (A)	I _{trip} @25°C (A)	P _d Typ. (W)	Maximum Time To Trip		Resistance	
							Current (A)	Time (Sec)	R _i min (Ω)	R ₁ max (Ω)
SMD0603-050	5	6.0	40	0.50	1.00	0.50	8.0	0.10	0.100	0.800

Order Information

Packaging

SMD0603	050	Tape & Reel Quantity
Product name	Hold Max	5,000 pcs/reel
Size 1508 mm / 0603 mils	Current voltage	
SMD: surface mount device	0.50A	

Recognition: UL Pending.