

SEA&LAND ELECTRONIC CORP.

13F.,No.120-10,
 Sec.3,Zhongshan Rd.,Zhonghe City,Taipei County,
 Taiwan, R.O.C.
 Tel.: 886-2-8221-2567
 Fax.: 886-2-2225-7268

Techfuse
PTC Devices
 Resettable Fuse

PRODUCT: R30-250
 DOCUMENT: QR0429
 ECN. NO.:
 REV LETTER:
 REV DATE: 2010/7/1
 PAGE NO.: 1 of 1

Specification Sheet

Insulating Material:
 meets UL94 V-0 Requirements
 Lead-free, RoHS Compliant

Lead Material:
 Tin plated copper-clad steel, 24AWG (0.020"Dia)

Marking:

- Sea&Land Logo
- TL**
- R30 - Radial type 30V
- 250 - hold current
- XXXX - Date code & Factory code




TABLE I. DIMENSIONS:

	A	B	C	D	E	F
	MAX	MAX	TYP	MIN	MAX	MAX
mm	11.4	18.3	5.1	7.6	3.0	1.2
in	0.45	0.72	0.20	0.30	0.12	0.05

TABLE II. PERFORMANCE RATINGS:

Model	V _{max} (Vdc)	I _{max} (A)	I _{hold} @25 °C (A)	I _{trip} @25 °C (A)	P _d Typ. (W)	Maximum Time To Trip		Resistance		
						Current (A)	Time (Sec)	Rimin (Ω)	Rimax (Ω)	R1max (Ω)
R30-250	30	40	2.50	5.00	1.2	12.5	10.3	0.020	0.040	0.070

Order Information

Packing

R30	250	K or S	R or U	Model	Reel Q'ty	Bag Q'ty
Radial type 30 V (A)	Hold Current (A)	K= Kink leads S= Straight leads	R= Tape & reel U= Bulk packaged	R30-250	3000	500

Tape & Reel packaging per EIA468-B sta

Recognition: UL / TÜV, approved.

E319079/NO.43486

