

SEA&LAND ELECTRONIC CORP.

13F.,No.120-10,
 Sec.3,Zhongshan Rd.,Zhonghe City,Taipei County,
 Taiwan, R.O.C.
 Tel.: 886-2-8221-2567
 Fax.: 886-2-2225-7268

Techfuse
PTC Devices
 Resettable Fuse


PRODUCT: R30-600
 DOCUMENT: QR0429
 ECN. NO.:
 REV LETTER:
 REV DATE: 2010/7/1
 PAGE NO.: 1 of 1

Specification Sheet

Insulating Material:
 meets UL94 V-0 Requirements
 Lead-free, RoHS Compliant

Lead Material:
 Tin plated copper, 20AWG (0.032"Dia)

Marking:

Sea&Land Logo


- R30 - Radial type 30V
- 600 - hold current
- XXXX - Date code & Factory code




TABLE I. DIMENSIONS:

	A	B	C	D	E	F
	MAX	MAX	TYP	MIN	MAX	MAX
mm	16.5	24.9	10.2	7.6	3.0	1.2
in	0.65	0.98	0.40	0.30	0.12	0.05

TABLE II. PERFORMANCE RATINGS:

Model	V _{max} (Vdc)	I _{max} (A)	I _{hold} @25 °C (A)	I _{trip} @25 °C (A)	P _d Typ. (W)	Maximum Time To Trip		Resistance		
						Current (A)	Time (Sec)	R _{imin} (Ω)	R _{imax} (Ω)	R _{1max} (Ω)
R30-600	30	40	6.00	12.00	3.5	30.0	16.0	0.005	0.020	0.040

Order Information

Packing

R30	600	K or S	R or U	Model	Reel Q'ty	Bag Q'ty
Radial type 30 V (A)	Hold Current (A)	K= Kink leads S= Straight leads	R= Tape & reel U= Bulk packaged	R30-600	-	500

Tape & Reel packaging per EIA468-B star

Recognition: UL / TÜV, approved.

E319079/NO.43486

