

**SEA&LAND ELECTRONIC CORP.**

13F., No.120-10,  
 Sec. 3, Zhongshan Rd., Zhonghe Dist., New Taipei City 235,  
 Taiwan  
 Tel.: 886-2-8221-2567  
 Fax.: 886-2-2225-7268

**Techfuse**  
**PTC Devices**  
 Resettable Fuse

PRODUCT: mSMD350  
 DOCUMENT: QR0429  
 ECN. NO.:  
 REV LETTER:  
 REV DATE: 2021-3-10  
 PAGE NO.: 1 of 1

# Specification Sheet


Terminal Pad Solderability:  
 Meets EIA Specification RS186-9E  
 And ANSI/J-STD-002 Category 3.

Terminal Pad Materials:  
 Tin-plated Nickel-Copper

Lead-Free, RoHS Compliant

Marking:

$\alpha$  Alpha Logo  
 350 Part Identification



**TABLE I. DIMENSIONS:**

Model	A		B		C		D	E
	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Min.
mSMD350	4.37	4.73	3.07	3.41	0.50	1.30	0.30	0.25

Unit:mm

**TABLE II. PERFORMANCE RATINGS:**

Model	$V_{max}$ (V)	$I_{max}$ (A)	$I_{hold}$ @25°C (A)	$I_{trip}$ @25°C (A)	$P_d$ Typ. (W)	Maximum Time To Trip		Resistance	
						Current (A)	Time (Sec)	$Ri_{min}$ (Ω)	$R1_{max}$ (Ω)
mSMD350	6.0	100	3.50	6.00	2.0	10.0	4.00	0.008	0.030

## Order Information

## Packaging

mSMD1812	350	Tape & Reel Quantity
Product name	Hold Max	1500 pcs/reel
Size 4532 mm /1812 mils	Current voltage	
SMD: surface mount device	3.50A	

Recognition: TUV,approved.

R 50481056  
 2015/863/EU  
 EN14582

