

SEA&LAND ELECTRONIC CORP.

13F., No.120-10,
 Sec. 3, Zhongshan Rd., Zhonghe Dist., New Taipei City 235,
 Taiwan

Tel.: 886-2-8221-2567

Fax.: 886-2-2225-7268

Techfuse
PTC Devices
 Resettable Fuse

PRODUCT: mSMD020-60V

DOCUMENT: QR0429

ECN. NO.:

REV LETTER:

REV DATE: 2026/3/20

PAGE NO.: 1 of 1

Specification Sheet

Terminal Pad Solderability:
 Meets EIA Specification RS186-9E
 And ANSI/J-STD-002 Category 3.

Terminal Pad Materials:
 Tin-plated Nickel-Copper

Lead-Free, RoHS Compliant

Marking:

α Alpha Logo
 020 Part Identification




TABLE I. DIMENSIONS:

Model	A		B		C		D	E
	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Min.
mSMD020-60V	4.37	4.73	3.07	3.41	0.50	1.30	0.30	0.25

Unit:mm

TABLE II. PERFORMANCE RATINGS:


Model	V_{max} (V)	I_{max} (A)	I_{hold} @25°C (A)	I_{trip} @25°C (A)	P_d Typ. (W)	Maximum Time To Trip		Resistance	
						Current (A)	Time (Sec)	$R_{i_{min}}$ (Ω)	$R_{1_{max}}$ (Ω)
mSMD020-60V	60	100	0.20	0.40	0.8	8.0	0.02	0.350	5.000

mSMD1812	020-60V	Tape & Reel Quantity
Product name	Hold	1500 pcs/reel
Size 4532 mm / 1812 mils	Current	
SMD: surface mount device	0.20A	

Recognition:

Agency Approvals :  E201504/E319079

 R 50481056

 CQC25001473187
 GB 4943.1-2022; IEC 60730-1 : 2013 15、17、J.15、J.17; GB/T 7153-

Regulation/Standard: 2015/863/EU



EN14582

