

SEA&LAND ELECTRONIC CORP.

13F., No.120-10,
 Sec. 3, Zhongshan Rd., Zhonghe Dist., New Taipei City 235,
 Taiwan
 Tel.: 886-2-8221-2567
 Fax.: 886-2-2225-7268

Techfuse
PTC Devices
 Resettable Fuse

PRODUCT: SMD0603-020
 DOCUMENT: QR0429
 ECN. NO.:
 REV LETTER: A
 REV DATE: 2011-3-29
 PAGE NO.: 1 of 1

Specification Sheet

Terminal Pad Solderability:
 Meets EIA Specification RS186-9E
 And ANSI/J-STD-002 Category 3.

Terminal Pad Materials:
 Tin-plated Nickel-Copper

Lead-Free, RoHS Compliant

Marking:
 Part Identification
 2= 020




TABLE I. DIMENSIONS:

Model	Marking	A		B		C		D
		Min.	Max.	Min.	Max.	Min.	Max.	Min.
SMD0603-020	2	1.45	1.85	0.65	1.05	0.40	1.00	0.15

Unit:mm

TABLE II. PERFORMANCE RATING:

Model	Marking	V _{max} (Vdc)	I _{max} (A)	I _{hold} @25°C (A)	I _{trip} @25°C (A)	P _d Typ. (W)	Maximum Time To Trip		Resistance	
							Current (A)	Time (Sec)	R _{i_min} (Ω)	R _{1_max} (Ω)
SMD0603-020	2	9.0	40	0.20	0.50	0.50	1.0	0.60	0.550	3.500

Order Information

Packaging

SMD0603	020	Tape & Reel Quantity
Product name	Hold Max	5,000 pcs/reel
Size 1508 mm / 0603 mils	Current voltage	
SMD: surface mount device	0.20A	

Recognition: UL Pending.