

**SEA&LAND ELECTRONIC CORP.**

13F., No.120-10,  
 Sec. 3, Zhongshan Rd., Zhonghe Dist., New Taipei City 235,  
 Taiwan  
 Tel.: 886-2-8221-2567  
 Fax.: 886-2-2225-7268

**Techfuse**  
**PTC Devices**  
 Resettable Fuse

PRODUCT: SL0805400  
 DOCUMENT: QR0429  
 ECN. NO.:  
 REV LETTER: A  
 REV DATE: 2026/4/28  
 PAGE NO.: 1 of 1


# Specification Sheet

Terminal Pad Solderability:  
 Meets EIA Specification RS186-9E  
 And ANSI/J-STD-002 Category 3.

Terminal Pad Materials:  
 Tin-plated Nickel-Copper

Lead-Free, RoHS Compliant

Marking:  
 Part Identification



**TABLE I. DIMENSIONS:**

Model	Marking	A		B		C		D
		Min.	Max.	Min.	Max.	Min.	Max.	Min.
SL0805400		1.9	2.5	1.2	1.8	0.6	1.2	0.2

Unit:mm

**TABLE II. PERFORMANCE RATINGS:**

Model	Marking	V <sub>max</sub> (Vdc)	I <sub>max</sub> (A)	I <sub>hold</sub> @25°C (A)	I <sub>trip</sub> @25°C (A)	P <sub>d</sub> Typ. (W)	Maximum Time To Trip		Resistance	
							Current (A)	Time (Sec)	R <sub>i_min</sub> (Ω)	R <sub>1_max</sub> (Ω)
SL0805400		6	50	4.00	8.00	1.2	16.0	5.0	0.0010	0.0180

**Order Information**

**Packaging**

SL0805	400	Tape & Reel Quantity
Product name	Hold	3,000 pcs/reel
Size 2012 mm / 0805 mils	Current	
SL: surface mount device	4.00A	

Recognition:

**UL Pending**

2015/863/EU



EN14582

