

SEA&LAND ELECTRONIC CORP.

13F., No.120-10,
 Sec. 3, Zhongshan Rd., Zhonghe Dist.,New Taipei City 235,
 Taiwan
 Tel.: 886-2-8221-2567
 Fax.: 886-2-2225-7268

Techfuse
PTC Devices
 Resettable Fuse

PRODUCT: SMD0805-010-24V
 DOCUMENT: QR0429
 ECN. NO.:
 REV LETTER: A
 REV DATE: 2026/3/18
 PAGE NO.: 1 of 1

Specification Sheet

Terminal Pad Solderability:
 Meets EIA Specification RS186-9E
 And ANSI/J-STD-002 Category 3.

Terminal Pad Materials:
 Tin-plated Nickel-Copper

Lead-Free, RoHS Compliant

Marking:

Part Identification
 1 = 010




TABLE I. DIMENSIONS:

Model	Marking	A		B		C		D	E
		Min.	Max.	Min.	Max.	Min.	Max.	Min.	Min.
SMD0805-010-24V	1	1.90	2.20	1.20	1.50	0.50	1.00	0.20	0.10

Unit:mm

TABLE II. PERFORMANCE RATINGS:

Model	Marking	V _{max} (Vdc)	I _{max} (A)	I _{hold} @25°C (A)	I _{trip} @25°C (A)	P _d Typ. (W)	Maximum Time To Trip		Resistance	
							Current (A)	Time (Sec)	R _{i_min} (Ω)	R _{1_max} (Ω)
SMD0805-010-24V	1	24	100	0.10	0.30	0.5	0.5	1.50	1.000	6.000

Order Information

Packaging

SMD0805	010-24V	Tape & Reel Quantity
Product name	Hold Max	5,000 pcs/reel
Size 2012 mm / 0805 mils	Current voltage	
SMD: surface mount device	0.10A	

Agency Approvals :



E201504(Alpha-Top)/E319079(Sea&Land)



CQC25001473187

GB 4943.1-2022;IEC 60730-1 : 2013 15、17、J.15、J.17;GB/T 7153-2002

Regulation/Standard:



2015/863/EU



EN14582